PV



simex.it



VIBRATING PLATE COMPACTORS

PV 300 PV 450 PV 600 PV 700



Designed to **compact any surface**, Simex PV vibrating plate compactors are an excellent solution for **achieving a solid**, **even**, **and well compacted bottom** that will never give way.

Possibility to mount the rotation device allows compaction in any position and in the most difficult-to-reach spots.

No routine maintenance is needed.







ADVANTAGES

- Precision
- Maintenance-free
- Versatile

DATI TECNICI		PV 300	PV 450	PV 600	PV 700	PV 850
Recommended excavator weight	ton	1,5 - 5	4 - 10	6 - 15	12 - 25	20 - 40
	Ibs	3300 - 11000	8800 - 22000	13000 - 33000	26400 - 55000	44000 - 88000
Plate dimensions	mm	290 x 710	440 x 710	550 x 890	710 x 1160	860 x 1110
	inch	11 x 28	17 x 28	22 x 35	28 x 45	34 x 44
Vibration frequency	n/min vpm	2100	2100	2100	2100	2100
Compaction force	kN	15	27	34	68	93
	lbf	3400	6000	7650	15300	20900
Weight without bracket (1)	kg	190	300	410	875	1 040
	Ibs	420	660	900	1925	2300
Required oil pressure	BAR	160	160	160	160	160
	psi	2320	2320	2320	2320	2320
Required oil flow	l/min gpm	30 8	57 15	75 20	110 29	155 41

(1) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements.

Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.

